

# STOWAWAY

---

## Tech Carts & Lecterns



PCR-1842-MB\_

24"D X 18"W X 42"H

# STOWAWAY



PCLD-1842-MB-LL  
Drawers  
Pullout Left



PCR-1842-MB-LL  
Vented Cabinet  
Pullout Right



Perforated Steel  
Vented Panel  
(Rear View)

## STOWAWAY PERSONAL CABINET

- Personal cabinets are available with either box and file drawers or a vented storage cabinet.
- Right or left side pullouts expand work areas.
- Personal cabinets feature a high pressure laminate work surface.
- Available in melamine or high pressure laminate with PVC edges or veneer with wood edges.
- Wire management grommet and casters are standard.
- Vented steel front panel.
- Customize with your organization's logo.
- Locks are optional on drawers and doors.

### EDGE TYPES



C  
3mm  
PVC



E  
3mm  
Wood

### CABINET



Vented  
Storage  
Cabinet



Box and File  
Drawers



Pullouts  
Left or  
Right

### PULLS



P1



P2



P3



P4



P5

### STOWAWAY STANDARD SIZES

MODEL	HEIGHT"	DEPTH"	WIDTH"
<b>CABINET</b>			
PC_-1842-MB-__	42	24	18
<b>DRAWER</b>			
PC_D-1842-MB-__	42	24	18

### To Order, Choose Finish Selections & Options

**Work Surface:** Choose from our selection of high pressure laminates.

**Cabinet:** Choose your high pressure laminate, thermally fused laminate or wood veneer.

**Edges:** Choose your PVC edgeband for high pressure laminate and melamine, choose a wood edge for veneer cabinets.

**Door/Frame:** Choose from our selection of Powder Coats.

See **MTContract's** Finish and Color Guide for choices at <https://www.mtcontract.com/resources/finishes>

### CASTERS



Twin Wheel  
Locking

### General Specifications

**Top:** Top is 1-1/4" thick, three ply engineered wood construction with .050" high pressure laminate, HPL, and a phenolic backer sheet. All edges are 3mm PVC with 1/8" radius top and bottom. Top is fitted with a 50mm diameter wire grommet.

**Case Construction:** Cabinet case is constructed of 3/4" thick thermofused melamine/ particle board panel material OR with three ply vertical grade HPL with 3mm PVC edge. Case is assembled using glue and dowel construction with blind pocket screw reinforcement where appropriate. Case is mounted to steel frame with threaded fasteners. Structural back panel is 18 ga. perforated steel for ventilation. A grommet may be specified in the bottom panel and/or base of side panels.

**Upper Shelf:** A fixed upper shelf of 3/4" thick thermofused melamine/particle board panel is provided. The exposed edges are edged with 3mm PVC.

**Slide out Shelf:** Slide out shelf is mounted near the top of the unit and extends out of the case to the right or to the left from the user side. Shelf is 3/4" thermofused melamine and is mounted on ball bearing drawer slides. Shelf is capped with an arched piece of hardwood that serves as a pull.

**Drawers:** Two lower drawers are provided. Drawers are constructed of 3/4" thick thermofused melamine/particle board panel material OR with three ply vertical grade HPL with 3mm PVC edge. Drawer hardware includes ball bearing drawer slides and a choice of standard pull styles.

**Steel Base Frame:** Base is a rectangular welded frame using 1-1/4" square section steel tubing. Casters are mounted into threaded inserts welded into the frame. Frame is powder coated.

**Casters:** Casters are 75mm twin wheel swivel type with brake rated for a minimum of 100 lb. each.



892 Industrial Park Drive  
Shelby, MI 49455  
P: 231.861.2194 | F: 231.861.6678  
[www.mtcontract.com](http://www.mtcontract.com)  
[sales@mediatechnologies.com](mailto:sales@mediatechnologies.com)

cs-stowaway-200826

PURE MICHIGAN®